



# Honeywell Home Universal Thermostat

## T4 Programmable Thermostat

T4 is a modern wired or wireless 7-day Programmable Room Thermostat. It is designed to provide automatic time and temperature control of heating in domestic or light commercial premises.

- Compatible with all bus enabled boilers and BCM devices
- On screen text display and function buttons to ensure simplified programming and operation for all users
- Energy saving 'fuzzy logic' control
- Optimum Stop, Start & Delayed Stop features that learn how the room is heated
- Easy to fit
- Wired version has a new improved wall plate with extra wiring space and a clip-on cover to the fixed wall plate
- Optional Wired external sensor available (wired versions only)
- On-screen heat demand icon makes start up testing easy
- Simple push button access to configuration menus
- Adjustable Frost protection
- Away mode with specific temperature set (number of days changeable)
- Temporary schedule override until next set point or for 1 or 2 hours
- Schedule can be turned off – will operate as a variable setting thermostat only
- Continuous time, displayed in extra-large LCD
- Automatic summer/winter time change
- 7-day programming with 7 day; 5/2 or single day schedules
- Four or six independent time & temperature settings (default is 4)
- Pre-configured 5/2 heating schedule
- Battery powered (with low-power indicator)
- Easy change battery compartment
- Optional backlight with extended light on time period
- Burner 'ON' symbol

## Wireless programmable thermostat additional features and benefits (T4R)

- Wireless communication between thermostat and receiver box with 30m range.
- Pre-bound to the wireless receiver box, no need to establish a binding

## Receiver box (wireless version only)

Designed for the installer in mind, this receiver box comes pre-bound to the T4R and provides the link between the boiler and the wireless thermostat.

- Lift up wiring bar for easy wiring
- OpenTherm terminals as standard
- Clear wiring labels
- Strain relief
- 4 screw fixing
- 2 Channel version available for 2 zone applications